

Technical Specifications

Version 1.0 March 2003

ARCHITECTURE

The ULTRAPATCH PX1000 allows to patch the audio signals of most components in your studio from a central point and send them to other units, which makes your entire cabling better structured and is indispensable for professional work. If you want to use your studio as effectively as possible then it is preferable to use a complete patchbay wiring scheme, but even less sophisticated patchbay solutions will benefit smaller studio configurations.

With the BEHRINGER ULTRAPATCH PX1000 you will own an easy-to-use 48-point balanced patchbay offering fully balanced high-quality 1/4" TRS connectors. Each channel can be aligned in 5 different modes.

FEATURES

- Professional and multi-functional 48-point balanced patchbay for studio and stage
- Each channel can be aligned in 5 different modes, giving you highest possible flexibility
- Fully balanced high-quality 1/4" TRS connectors
- Super-rugged metal construction for long life and durability
- Manufactured under ISO9000 certified management system

SPECIFICATIONS

Dimensions

Weight

Connectors

Height 1 3/4" (44.5 mm) Width 19" (482.6 mm) Depth 2 3/4" (69.3 mm) approx. 1.3 kg (2 7/8 lbs) 1/4" TRS balanced

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

The information contained in this sheet is subject to change without notice. No part of this sheet may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH. BEHRINGER is a registered trademark. ALL RIGHTS RESERVED.

© 2003 BEHRINGER Spezielle Studiotechnik GmbH

BEHRINGER Spezielle Studiotechnik GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany Tel. +49 (0) 21 54/92 06-0, Fax +49 (0) 21 54/92 06-30

