

# **Hypersonic 2**

# Read Me – Universal Binary Update

Steinberg Media Technologies GmbH April 2007





### What is new?

This Universal Binary update brings support for the Mac Intel platform.

#### **Download instructions**

- Download "Hypersonic2\_UB\_Update.dmg" file to your desktop.
- Double-click "Hypersonic2\_UB\_Update.dmg"
- The folder includes installer for VST, AU and Rewire.

#### **Installation**

### [1] Installation of Syncrosoft Licence Software

If you have already installed your Syncrosoft Licence Control Software please continue with step [2].

- Double-click the "SyncrosoftLicenceControl.mpkg" file located in the "Copy Protection Driver" folder of your product DVD. Follow the on-screen instruction.
- Make sure to have your Steinberg Key connected to your Mac.

# [2] Installation of Hypersonic 2 Universal Binary Plug-In

- Please double-click desired file (e.g. "Hypersonic 2 VST.pkg") to launch the installer.
- Follow the on-screen instructions.

### [3] Installation of Hypersonic Content Data

- Please drag the folder "Hypersonic 2 Content" from your product DVD onto your hard disk. You can put the folder anywhere you like, including external hard drives.
- When copying has finished, please open the "Hypersonic 2 Content" folder on your hard drive and double-click the file "Set HS2 Content Location". This tells the plug-in where to find the data.



# **Technical Support**

Steinberg product specialists are also on hand to provide individual assistance at:

### www.steinberg.net

Please note, in order to receive technical support and information, you have to register your product after Installing.

# **System requirements**

**Steinberg Key required.** (not included)

Macintosh	Windows
Minimum required:	Minimum required:
Mac OSX 10.4	Windows XP Home or XP Professional
Power Mac G4 1.25 GHz / Intel core Solo	Intel / AMD processor 1,4 GHz minimum
1.5 GHz	512 MB RAM
512 MB RAM	2 GB free HD space
2 GB free HD space	DVD-Rom required for Installation
DVD drive required for Installation	Windows MME compatible audio hardware
CoreAudio compatible audio hardware	(ASIO compatible audio hardware required
Steinberg Key and USB port required	for low latency operation.)
Internet Connection required for license	Steinberg Key and USB port required
activation	Internet Connection required for license activation
For using as plug-in or Rewire slave-device, a VST2, AU (tested in Logic 7.1.1 and	For using as plug-in or Rewire slave-device,
Digital Performer 4.6 only) or Rewire compatible Host is required.	a VST2, DXi2 or Rewire compatible Host is required.
(See Steinberg web for recommendations)	(See Steinberg web for recommendations)